

ESTIMATED LEAD TIMES

Clopay® Dealer Residential & Commercial

The tables below show the current **estimated lead times** from the order date to the Clopay dealer or Clopay Distribution Center. For an exact date, please check your order acknowledgement once the order is placed.



Residential Models	Estimated Lead Times
Avante® AV, AVI, AX	19 Week Lead Time
Canyon Ridge® CAN_, CRM_	17 Week Lead Time
Wood - Classic™ & Reserve® 10, 20_, 44_, CR800, CRD_, MRD_, RC_, RH_, RR_	7 Week Lead Time
Wood - Classic™ 33_	11 Week Lead Time
Coachman® - Polystyrene CD_, CG_	26 Week Lead Time
Coachman® - Intellicore® CGU_	17 Week Lead Time
Grand Harbor® GH_, GHV_	TBD
2" & 1 3/8" Intellicore® - Classic™, Modern, Gallery® & Bridgeport™ 913_, 920_, BD1_U, BD2_U, GD1_U, GD2_U	17 Week Lead Time
2" Polystyrene - Classic™, Modern & Gallery® 430_, 431_, GD2_P	26 Week Lead Time
1 3/8" Polystyrene - Classic™ & Modern 4050, 4051, 4053	14 Week Lead Time
1 3/8" Polystyrene - Modern & Gallery® 4132, 4138, GD1_P	26 Week Lead Time
Value & Value Plus - Classic™ & Gallery® 70B, 73 76, 76V, 94, 1500, GD4_, GD5_, T50S	14 Week Lead Time
Value & Value Plus - Classic™ & Modern 4F, T40_, T42_, T50L, T52_	11 Week Lead Time
Entry Doors Arbor Grove™, Rustic, Craftsman, and Steel Collection	7 Week Lead Time
Entry Doors Smooth Fiberglass Collection	TBD
Commercial Models	Estimated Lead Times
Full View / Glass 902_, 903, 904, FV_	19 Week Lead Time
3", 2", 1 3/4" & 1 3/8" Intellicore® 370_, 371_, 372_, 3730	17 Week Lead Time
2" & 1 3/8" Polystyrene 315_, 320_, 321_, 3220, CFR38, CFR68	26 Week Lead Time
1 Layer & 2 Layer 520, 520S, 522, 522S, 524, 524_, 525, 525_, 664, 664V	22 Week Lead Time

Exceptions

- ◆ Grand Harbor model doors and Smooth Fiberglass Entry Doors have an extended undefined lead-time due to continued material shortages. Orders for these models will be individually updated as materials become available and updated order acknowledgements will be sent out at
- ◆ Color Blast® orders - additional 6 weeks
- ◆ Powder coated track and hardware orders - additional 3 weeks
- ◆ Powder coated aluminum sections - additional 4 weeks
- ◆ Stainless steel track and hardware - additional 3 weeks
- ◆ High heat hollow stop mold - additional 4 weeks